

## A-5523100T

SWITCH 3P 32A.D1 ANTIMICROBIAL TREATMENT



|                            |                                                                                                                                                                                                                                                                                                                      |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Code</b>                | 009A-5523100T                                                                                                                                                                                                                                                                                                        |
| <b>EAN</b>                 | 8430892307567                                                                                                                                                                                                                                                                                                        |
| <b>Product description</b> | Cam switch-disconnector IP20. Kit of 0-1 front plate with antimicrobial treatment White color RAL 9010 64x64 for panel fixing. 3 poles 32A. Size D1. Ergonomic screwless quick-mount handle. Connection with cage terminals for 6-16 mm <sup>2</sup> cable. Compatible with multiple accessories from the A5 series. |

## Logistic data

|               |           |
|---------------|-----------|
| Customs code  | 85365080  |
| ETIM code     | EC000216? |
| Package units | 1         |

## Technical data

|                         |                        |
|-------------------------|------------------------|
| Poles                   | 3                      |
| Operational rating (Ie) | 32 A                   |
| Thermal rating (Ith)    | 40 A                   |
| Wire section (AWG)      | 6                      |
| Wire section rigid      | 6 - 25 mm <sup>2</sup> |
| Wire section flexible   | 6 - 16 mm <sup>2</sup> |
| Tightening torque       | 2 Nm                   |
| Connection screws       | M5                     |

### Terminal



|                                        |                                                                                                                                                                     |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max. fuse protection (gG/aM)           | 40/32 A (415 V)<br>40/32 A (500 V)                                                                                                                                  |
| Conditional shortcircuit current (Icc) | 6 kA (415 V)<br>6 kA (500 V)                                                                                                                                        |
| Insulating voltage (V~)                | 690                                                                                                                                                                 |
| Insulating voltage (V...)              | 600                                                                                                                                                                 |
| Dummy AC-21A                           | 11 kW (3x230 V)<br>18,5 kW (3x415 V)<br>22 kW (3x500 V)                                                                                                             |
| Mixed load AC-22A                      | 7,5 kW (3x230 V)<br>15 kW (3x415 V)<br>18,5 kW (3x500 V)                                                                                                            |
| Motor load AC-23A                      | 5,5 kW (3x230 V)<br>11 kW (3x415 V)<br>15 kW (3x500 V)                                                                                                              |
| UL Electric characteristics            | 2 hp 1-fase (110-120 V)<br>3 hp 1-fase (220-240 V)<br>7,5 hp 3-fase (220-240 V)<br>10 hp 3-fase (380-415 V)<br>10 hp 3-fase (440-480 V)<br>15 hp 3-fase (550-600 V) |
| Standard                               | IEC 60947-3<br>UL 508                                                                                                                                               |
| Handle type                            | Directo antimicrobiano                                                                                                                                              |

## Dimensions

