

A-560C100

CHANGEOVER SWITCH 1P. 250A D3

Code	009A-560C100
EAN	8430892236836

Product description

Changeover cam switch, IP20 with 1-0-2 grey front plate 64x64 for panel fixing. 1 pole 250A. Size D3. Ergonomic screwless quick-mount handle. Cable lug terminal connection for 120 mm² cable. Compatible with multiple accessories from the A5 series.

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1
Package height (mm)	167
Package width (mm)	121
Package length (mm)	106

Technical data


Poles	1
Operational rating (I _e)	250 A
Thermal rating (I _{th})	250 A
Wire section flexible	120 mm ²
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	250 A (415 V) 250 A (500 V)
Conditional shortcircuit current (I _{cc})	8 kA (415 V) 8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	75 kW (3x230 V) 132 kW (3x415 V) 160 kW (3x500 V)
Mixed load AC-22A	75 kW (3x230 V) 132 kW (3x415 V) 132 kW (3x500 V)
Motor load AC-23A	75 kW (3x230 V) 110 kW (3x415 V)
Standard	IEC 60947-3
Handle type	Directo

Connection



Dimensions

