

## A-5619100

CHANGEOVER SWITCH 2P 125A.D2




<b>Code</b>	009A-5619100
<b>EAN</b>	8430892170819
<b>Product description</b>	Changeover cam switch, IP20 with 1-0-2 grey front plate 64x64 for panel fixing. 2 poles 125A. Size D2. Ergonomic screwless quick-mount handle. Connection with cage terminals for 16-50 mm <sup>2</sup> cable. Compatible with multiple accessories from the A5 series.

**Logistic data**


---

Customs code	85365080
ETIM code	EC000216
Package units	1
Product gross weight (kg)	0.54
Package height (mm)	163
Package width (mm)	88
Package length (mm)	86

## Technical data

<b>Poles</b>	2
<b>Operational rating (Ie)</b>	125 A
<b>Thermal rating (Ith)</b>	125 A
<b>Wire section (AWG)</b>	16 - 1
<b>Wire section flexible</b>	16 - 50 mm <sup>2</sup>
<b>Tightening torque</b>	3,5 Nm
<b>Connection screws</b>	M8
<b>Terminal</b>	
<b>Max. fuse protection (gG/aM)</b>	125/100 A (415 V) 125/100 A (500 V)
<b>Conditional shortcircuit current (Icc)</b>	8 kA (415 V) 8 kA (500 V)
<b>Insulating voltage (V~)</b>	690
<b>Insulating voltage (V...)</b>	600
<b>Dummy AC-21A</b>	37 kW (3x230 V) 75 kW (3x415 V) 90 kW (3x500 V)
<b>Mixed load AC-22A</b>	37 kW (3x230 V) 55 kW (3x415 V) 75 kW (3x500 V)
<b>Motor load AC-23A</b>	18,5 kW (3x230 V) 37 kW (3x415 V) 45 kW (3x500 V)
<b>UL Electric characteristics</b>	10 hp 1-fase (110-120 V) 15 hp 1-fase (220-240 V) 25 hp 3-fase (220-240 V) 30 hp 3-fase (380-415 V) 40 hp 3-fase (440-480 V) 50 hp 3-fase (550-600 V)
<b>Standard</b>	IEC 60947-3 UL 508
<b>Handle type</b>	Directo

Connection



Dimensions

