

A-570A100

CHANGEOVER SWITCH WITHOUT 0 1P 160A.D3

| | |
|-------------|---------------|
| Code | 009A-570A100 |
| EAN | 8430892170864 |

Product description

Changeover cam switch, IP20 with 1-2 grey front plate 64x64 for panel fixing. 1 pole 160A. Size D3. Ergonomic screwless quick-mount handle. Cable lug terminal connection for 70 mm² cable. Compatible with multiple accessories from the A5 series.

Logistic data

| | |
|---------------|----------|
| Customs code | 85365080 |
| ETIM code | EC000216 |
| Package units | 1 |

Technical data

| | |
|--------------------------------------|--------------------|
| Poles | 1 |
| Operational rating (I _e) | 160 A |
| Thermal rating (I _{th}) | 160 A |
| Wire section flexible | 70 mm ² |
| Connection screws | M8 |

Terminal



| | |
|------------------------------|---------------|
| Max. fuse protection (gG/aM) | 160 A (415 V) |
| | 160 A (500 V) |

| | |
|---|--------------|
| Conditional shortcircuit current (I _{cc}) | 8 kA (415 V) |
| | 8 kA (500 V) |

| | |
|-------------------------|-----|
| Insulating voltage (V~) | 690 |
|-------------------------|-----|

| | |
|---------------------------|-----|
| Insulating voltage (V...) | 600 |
|---------------------------|-----|

| | |
|--------------|------------------|
| Dummy AC-21A | 45 kW (3x230 V) |
| | 90 kW (3x415 V) |
| | 110 kW (3x500 V) |


| | |
|-------------------|-----------------|
| Mixed load AC-22A | 37 kW (3x230 V) |
| | 75 kW (3x415 V) |
| | 90 kW (3x500 V) |

| | |
|-------------------|-----------------|
| Motor load AC-23A | 30 kW (3x230 V) |
| | 52 kW (3x415 V) |
| | 65 kW (3x500 V) |

| | |
|----------|-------------|
| Standard | IEC 60947-3 |
|----------|-------------|

| | |
|-------------|---------|
| Handle type | Directo |
|-------------|---------|

Connection



Dimensions

