

# A-5764100

CHANGEOVER SWITCH WITHOUT 0 6P 40A.D1

|             |               |
|-------------|---------------|
| <b>Code</b> | 009A-5764100  |
| <b>EAN</b>  | 8430892103404 |

## Product description

Changeover cam switch, IP20 with 1-2 grey front plate 64x64 for panel fixing. 6 pole 40A. Size D1. Ergonomic screwless quick-mount handle. Connection with cage terminals for 6-16 mm<sup>2</sup> cable. Compatible with multiple accessories from the A5 series.

## Logistic data

|                     |          |
|---------------------|----------|
| Customs code        | 85365080 |
| ETIM code           | EC000216 |
| Package units       | 1        |
| Package height (mm) | 155      |
| Package width (mm)  | 70       |
| Package length (mm) | 70       |

## Technical data

|                                      |                        |
|--------------------------------------|------------------------|
| Poles                                | 6                      |
| Operational rating (I <sub>e</sub> ) | 40 A                   |
| Thermal rating (I <sub>th</sub> )    | 40 A                   |
| Wire section (AWG)                   | 6                      |
| Wire section rigid                   | 6 - 25 mm <sup>2</sup> |
| Wire section flexible                | 6 - 16 mm <sup>2</sup> |
| Tightening torque                    | 2 Nm                   |
| Connection screws                    | M5                     |

### Terminal



|                                                     |                                                                                                                                                                     |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max. fuse protection (gG/aM)                        | 40/32 A (415 V)<br>40/32 A (500 V)                                                                                                                                  |
| Conditional shortcircuit current (I <sub>cc</sub> ) | 6 kA (415 V)<br>6 kA (500 V)                                                                                                                                        |
| Insulating voltage (V~)                             | 690                                                                                                                                                                 |
| Insulating voltage (V...)                           | 600                                                                                                                                                                 |
| Dummy AC-21A                                        | 15 kW (3x230 V)<br>22 kW (3x415 V)<br>30 kW (3x500 V)                                                                                                               |
| Mixed load AC-22A                                   | 11 kW (3x230 V)<br>22 kW (3x415 V)<br>22 kW (3x500 V)                                                                                                               |
| Motor load AC-23A                                   | 11 kW (3x230 V)<br>18,5 kW (3x415 V)<br>22 kW (3x500 V)                                                                                                             |
| UL Electric characteristics                         | 2 hp 1-fase (110-120 V)<br>5 hp 1-fase (220-240 V)<br>7,5 hp 3-fase (220-240 V)<br>10 hp 3-fase (380-415 V)<br>15 hp 3-fase (440-480 V)<br>20 hp 3-fase (550-600 V) |
| Standard                                            | IEC 60947-3<br>UL 508                                                                                                                                               |
| Handle type                                         | Directo                                                                                                                                                             |

Connection

