

## A-6022100

CHANGEOVER SWITCH WITHOUT 0 3P 5 POS.25A.D1

<b>Code</b>	009A-6022100
<b>EAN</b>	8430892104197

---

**Product description**

Changeover step switch, IP20 with 1-2-3-4-5 grey front plate 64x64 for panel fixing. 3 poles 25A. Size D1. Ergonomic screwless quick-mount handle. Connection with cage terminals for 6-16 mm<sup>2</sup> cable. Compatible with multiple accessories from the A5 series.

---

## Logistic data

Customs code	85365080
ETIM code	EC002611
Package units	1
Package height (mm)	210
Package width (mm)	82
Package length (mm)	82

## Technical data

Poles	3
Operational rating (Ie)	25 A
Thermal rating (Ith)	25 A
Wire section (AWG)	6
Wire section rigid	6 - 25 mm <sup>2</sup>
Wire section flexible	6 - 16 mm <sup>2</sup>
Tightening torque	2 Nm
Connection screws	M5

### Terminal



Max. fuse protection (gG/aM)	25/25 A (415 V)
	25/25 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	7,5 kW (3x230 V)
	15 kW (3x415 V)
	18,5 kW (3x500 V)
Mixed load AC-22A	7,5 kW (3x230 V)
	15 kW (3x415 V)
	18,5 kW (3x500 V)
Motor load AC-23A	5,5 kW (3x230 V)
	7,5 kW (3x415 V)
	11 kW (3x500 V)
UL Electric characteristics	2 hp 1-fase (110-120 V)
	3 hp 1-fase (220-240 V)
	2 hp 3-fase (220-240 V)
	3 hp 3-fase (380-415 V)
	5 hp 3-fase (440-480 V)
	7 hp 3-fase (550-600 V)
Standard	IEC 60947-3
	UL 508
Handle type	Directo

Connection

29	30			X		
27	28				X	
25	26		X			
23	24				X	
21	22	X				
19	20				X	
17	18		X			
15	16				X	
13	14	X				
11	12			X		
9	10			X		
7	8				X	
5	6		X			
3	4				X	
1	2	X				
602		1	2	3	4	5

