

A-6436100

REVERSING STAR DELTA CHANGEOVER SWITCH 63A.D2

Code	009A-6436100
-------------	--------------

EAN	8430892105842
------------	---------------

Product description

Reversing star-delta changeover switch, IP20 with Δ -*0-* Δ grey front plate 64x64 for panel fixing, 63A. Size D1. Ergonomic screwless quick-mount handle. Connection with cage terminals for 16-50 mm² cable. Compatible with multiple accessories from the A5 series.


Logistic data

Customs code	85365080
ETIM code	EC002611
Package units	1
Package height (mm)	210
Package width (mm)	82
Package length (mm)	82

Technical data

Poles	3
Operational rating (Ie)	63 A
Thermal rating (Ith)	70 A
Wire section (AWG)	16 - 1
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	63/63 A (415 V)
	63/63 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	22 kW (3x230 V)
	45 kW (3x415 V)
	45 kW (3x500 V)
Mixed load AC-22A	18,5 kW (3x230 V)
	37 kW (3x415 V)
	45 kW (3x500 V)
Motor load AC-23A	15 kW (3x230 V)
	22 kW (3x415 V)
	30 kW (3x500 V)
UL Electric characteristics	5 hp 1-fase (110-120 V)
	10 hp 1-fase (220-240 V)
	15 hp 3-fase (220-240 V)
	25 hp 3-fase (380-415 V)
	30 hp 3-fase (440-480 V)
	32 hp 3-fase (550-600 V)
Standard	IEC 60947-3 UL 508
Handle type	Directo

Connection

19	20	X	X		X	X
17	18	X				X
15	16		X		X	
13	14		X		X	
11	12	X				X
9	10	X				X
7	8				X	X
5	6	X	X			
3	4	X	X			
1	2				X	X
643		△	λ	0	λ	△

