

# A-7673100

AMMETER CHANGEOVER SWITCH 3CIRCUITS TRANSFORMER 32A.D1

**Code**

009A-7673100

**EAN**

8430892107020

**Product description**

3 circuits ammeter switch (with transformer) , IP20 with 0-R-S-T grey front plate 64x64 for panel fixing. 32A. Size D1. Ergonomic screwless quick-mount handle. Connection with cage terminals for 6-16 mm<sup>2</sup> cable. Compatible with multiple accessories from the A5 series.

## Logistic data


|               |          |
|---------------|----------|
| Customs code  | 85365080 |
| ETIM code     | EC000216 |
| Package units | 1        |

## Technical data

|                         |                        |
|-------------------------|------------------------|
| Poles                   | NA/NA                  |
| Operational rating (Ie) | 32 A                   |
| Thermal rating (Ith)    | 40 A                   |
| Wire section (AWG)      | 6                      |
| Wire section rigid      | 6 - 25 mm <sup>2</sup> |
| Wire section flexible   | 6 - 16 mm <sup>2</sup> |
| Tightening torque       | 2 Nm                   |
| Connection screws       | M5                     |

|                                        |                                                                                                                                                                     |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Terminal                               |                                                                                  |
| Max. fuse protection (gG/aM)           | 40/32 A (415 V)<br>40/32 A (500 V)                                                                                                                                  |
| Conditional shortcircuit current (Icc) | 6 kA (415 V)<br>6 kA (500 V)                                                                                                                                        |
| Insulating voltage (V~)                | 690                                                                                                                                                                 |
| Insulating voltage (V...)              | 600                                                                                                                                                                 |
| Dummy AC-21A                           | 11 kW (3x230 V)<br>18,5 kW (3x415 V)<br>22 kW (3x500 V)                                                                                                             |
| Mixed load AC-22A                      | 7,5 kW (3x230 V)<br>15 kW (3x415 V)<br>18,5 kW (3x500 V)                                                                                                            |
| Motor load AC-23A                      | 5,5 kW (3x230 V)<br>11 kW (3x415 V)<br>15 kW (3x500 V)                                                                                                              |
| UL Electric characteristics            | 2 hp 1-fase (110-120 V)<br>3 hp 1-fase (220-240 V)<br>7,5 hp 3-fase (220-240 V)<br>10 hp 3-fase (380-415 V)<br>10 hp 3-fase (440-480 V)<br>15 hp 3-fase (550-600 V) |
| Standard                               | IEC 60947-3<br>UL 508                                                                                                                                               |
| Handle type                            | Directo                                                                                                                                                             |

## Connection



## Dimensions

