

AB551C100

ON-OFF SWITCH DISCONNECTOR 2P.250A D3 PADLOCKABLE RED/YELLOW

Code	009AB551C100
EAN	8430892215350

Product description

Padlockable on-off switch disconnecter, IP20 with red handle/yellow front plate 64x64 for panel fixing. 2 poles 250A. Size D3. Ergonomic screwless quick-mount handle. Cable lug terminal connection for 120 mm² cable. Compatible with multiple accessories from the A5 series.

Logistic data



Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	2
Operational rating (Ie)	250 A
Thermal rating (Ith)	250 A
Wire section flexible	120 mm²
Connection screws	M8

Terminal	
Max. fuse protection (gG/aM)	250 A (415 V) 250 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V) 8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	75 kW (3x230 V) 132 kW (3x415 V) 160 kW (3x500 V)
Mixed load AC-22A	75 kW (3x230 V) 132 kW (3x415 V) 132 kW (3x500 V)
Motor load AC-23A	75 kW (3x230 V) 110 kW (3x415 V)
Standard	IEC 60947-3
Handle type	Bloqueable candados

Connection



Dimensions

