

## AB5532126

ON-OFF SWITCH DISCONNECTOR 4 P.25A. WITH UNDERVOLTAGE RELEASE 230 V AC



<b>Code</b>	009AB5532126
<b>EAN</b>	8430892189057
<b>Product description</b>	On-Off switch disconnecter with undervoltage release 230V. Red/yellow padlockable handle panel fixing 66x66. 4 poles 25A. IP20 terminal connection for wires size 1-2,5 mm².

---

## Logistic data

---

Customs code 85365080

---

## Technical data

---

Poles	4
Operational rating (Ie)	25 A
Thermal rating (Ith)	25 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm <sup>2</sup>
Wire section flexible	2,5 - 6 mm <sup>2</sup>
Tightening torque	1,6 Nm
Connection screws	M4

---

Terminal



Max. fuse protection (gG/aM)	25/25 A (415 V)
	25/25 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	400
Dummy AC-21A	7,5 kW (3x230 V)
	15 kW (3x415 V)
	18,5 kW (3x500 V)
Mixed load AC-22A	7,5 kW (3x230 V)
	15 kW (3x415 V)
	18,5 kW (3x500 V)
Motor load AC-23A	5,5 kW (3x230 V)
	7,5 kW (3x415 V)
	11 kW (3x500 V)
Standard	IEC 60947-3
	UL 508
Handle type	Bloqueable candados

---

Connection

---

