AB5532126

ON-OFF SWITCH DISCONNECTOR 4 P.25A. WITH UNDERVOLTAGE RELEASE 230 V AC



Code	009AB5532126
EAN	8430892189057
Product description	On-Off switch disconnector with undervoltage release 230V. Red/yellow padlockable handle panel fixing 66x66. 4 poles 25A. IP20 terminal connection for wires size 1-2,5 mm².


Logistic data

Customs code	85365080

Technical data

Poles	4
Operational rating (Ie)	25 A
Thermal rating (Ith)	25 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm2
Wire section flexible	2,5 - 6 mm2
Tightening torque	1,6 Nm
Connection screws	M4
Terminal	
Max. fuse protection (gG/aM)	25/25 A (415 V) 25/25 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V) 6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	400
Dummy AC-21A	7,5 kW (3x230 V) 15 kW (3x415 V) 18,5 kW (3x500 V)
Mixed load AC-22A	7,5 kW (3x230 V) 15 kW (3x415 V) 18,5 kW (3x500 V)
Motor load AC-23A	5,5 kW (3x230 V) 7,5 kW (3x415 V) 11 kW (3x500 V)
Standard	IEC 60947-3 UL 508
Handle type	Bloqueable candados

Connection


N L1 L2 L3 PE
1 3
2 4
5
U1 V1 W1
U<
M
3~
Excitación = 85%
Desexcitación = 35...75%
Operación continua = 100%