

AB5532146

ON-OFF SWITCH DISCONNECTOR 4 P.25A. WITH UNDERVOLTAGE RELEASE 400 V AC



Code	009AB5532146
EAN	8430892189040
Product description	On-Off switch disconnecter with undervoltage release 400V. Red/yellow padlockable handle panel fixing 66x66. 4 poles 25A. IP20 terminal connection for wires size 1-2,5 mm ² .

Logistic data

Customs code 85365080

Technical data

Poles	4
Operational rating (Ie)	25 A
Thermal rating (Ith)	25 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm ²
Wire section flexible	2,5 - 6 mm ²
Tightening torque	1,6 Nm
Connection screws	M4

Terminal



Max. fuse protection (gG/aM)	25/25 A (415 V)
	25/25 A (500 V)

Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)

Insulating voltage (V~)	690
-------------------------	-----

Insulating voltage (V...)	400
---------------------------	-----

Dummy AC-21A	7,5 kW (3x230 V)
	15 kW (3x415 V)
	18,5 kW (3x500 V)

Mixed load AC-22A	7,5 kW (3x230 V)
	15 kW (3x415 V)
	18,5 kW (3x500 V)

Motor load AC-23A	5,5 kW (3x230 V)
	7,5 kW (3x415 V)
	11 kW (3x500 V)

Standard	IEC 60947-3
	UL 508

Handle type	Bloqueable candados
-------------	---------------------

Connection

