

## ABA534100

SWITCH 4P 40A D1 PADLOCKABLE 1NO



|      |               |
|------|---------------|
| Code | 009ABA534100  |
| EAN  | 8430892236799 |

## Logistic data

|               |          |
|---------------|----------|
| ETIM code     | EC002611 |
| Package units | 1        |

## Technical data

|                         |                        |
|-------------------------|------------------------|
| Poles                   | 4                      |
| Operational rating (Ie) | 40 A                   |
| Thermal rating (Ith)    | 40 A                   |
| Wire section (AWG)      | 6                      |
| Wire section rigid      | 6 - 25 mm <sup>2</sup> |
| Wire section flexible   | 6 - 16 mm <sup>2</sup> |
| Tightening torque       | 2 Nm                   |
| Connection screws       | M5                     |

### Terminal



|                                        |                                                                                                                                                                     |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max. fuse protection (gG/aM)           | 40/32 A (415 V)<br>40/32 A (500 V)                                                                                                                                  |
| Conditional shortcircuit current (Icc) | 6 kA (415 V)<br>6 kA (500 V)                                                                                                                                        |
| Insulating voltage (V~)                | 690                                                                                                                                                                 |
| Insulating voltage (V...)              | 600                                                                                                                                                                 |
| Dummy AC-21A                           | 15 kW (3x230 V)<br>22 kW (3x415 V)<br>30 kW (3x500 V)                                                                                                               |
| Mixed load AC-22A                      | 11 kW (3x230 V)<br>22 kW (3x415 V)<br>22 kW (3x500 V)                                                                                                               |
| Motor load AC-23A                      | 11 kW (3x230 V)<br>18,5 kW (3x415 V)<br>22 kW (3x500 V)                                                                                                             |
| UL Electric characteristics            | 2 hp 1-fase (110-120 V)<br>5 hp 1-fase (220-240 V)<br>7,5 hp 3-fase (220-240 V)<br>10 hp 3-fase (380-415 V)<br>15 hp 3-fase (440-480 V)<br>20 hp 3-fase (550-600 V) |
| Standard                               | IEC 60947-3<br>UL 508                                                                                                                                               |
| Handle type                            | Bloqueable candados                                                                                                                                                 |

Connection

---

