

AC5524100H

ON-OFF SWITCH DISCONNECTOR 3P 40A.D1 IP69K PADLOCKABLE BLACK/GREY HANDLE



Code	009AC5524100H
EAN	8430892314305

Product description

On-off switch disconnecter with IP69K safety padlockable handle. Black handle/grey plate with marking 0-I (0 12h 60°). Handle with hygienic design and use of antimicrobial technology. Switch body IP20. Multipole switch breaking 3P 40A. Size D1. Connection with cage terminals for 6-16 mm² cable.

Logistic data

Customs code	85365080
--------------	----------

Technical data

Poles	3
Operational rating (Ie)	40 A
Thermal rating (Ith)	40 A
Wire section (AWG)	6
Wire section rigid	6 - 25 mm ²
Wire section flexible	6 - 16 mm ²
Tightening torque	2 Nm
Connection screws	M5

Terminal



	40/32 A (415 V)
Max. fuse protection (gG/aM)	40/32 A (500 V)

	6 kA (415 V)
Conditional shortcircuit current (Icc)	6 kA (500 V)

Insulating voltage (V~)	690
Insulating voltage (V...)	600

	15 kW (3x230 V)
Dummy AC-21A	22 kW (3x415 V)
	30 kW (3x500 V)


	11 kW (3x230 V)
Mixed load AC-22A	22 kW (3x415 V)
	22 kW (3x500 V)

	11 kW (3x230 V)
Motor load AC-23A	18,5 kW (3x415 V)
	22 kW (3x500 V)

	2 hp 1-fase (110-120 V)
	5 hp 1-fase (220-240 V)
UL Electric characteristics	7,5 hp 3-fase (220-240 V)
	10 hp 3-fase (380-415 V)
	15 hp 3-fase (440-480 V)
	20 hp 3-fase (550-600 V)

Standard	IEC 60947-3 / UL 508
Handle type	IP69K
producte.Impact I K	IK10

Connection



Dimensions

