

## A-552012L4

COMBILIGHT ON-OFF SWITCH RED/GREEN 400V 3P 12A



<b>Code</b>	009A-552012L4
<b>EAN</b>	8430892257282
<b>Product description</b>	Combilight switch disconnecter by position 400vac, IP20 with 0-1 black front plate 48x48 for panel fixing, 0" red LED, "1" green LED. 3 poles 12A. Size D0. Ergonomic screwless quick-mount handle. Connection with cage terminals for 2.5-6 mm <sup>2</sup> cable. Compatible with multiple accessories from the A5 series. "

---

## Logistic data

---

Customs code	85365080
ETIM code	EC000216
Package units	1

## Technical data

---

Poles	3
Operational rating (Ie)	12A
Thermal rating (Ith)	16 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm <sup>2</sup>
Wire section flexible	2,5 - 6 mm <sup>2</sup>
Tightening torque	1,6 Nm
Connection screws	M4

Terminal



Max. fuse protection (gG/aM)

25/25 A (415 V)  
25/25 A (500 V)

Conditional shortcircuit current (Icc)

6 kA (415 V)  
6 kA (500 V)

Insulating voltage (V~)

690

Insulating voltage (V...)

400

Dummy AC-21A

3 kW (3x230 V)  
7,5 kW (3x415 V)  
11 kW (3x500 V)

Mixed load AC-22A

2,2 kW (3x230 V)  
5,5 kW (3x415 V)  
7,5 kW (3x500 V)

Motor load AC-23A

2,2 kW (3x230 V)  
4 kW (3x415 V)  
5,5 kW (3x500 V)

UL Electric characteristics

1 hp 1-fase (110-120 V)  
1,5 hp 1-fase (220-240 V)  
1 hp 3-fase (220-240 V)  
2 hp 3-fase (380-415 V)  
3 hp 3-fase (440-480 V)  
3 hp 3-fase (550-600 V)

Standard

IEC 60947-3  
UL 508

## Connection

---

5	6		×
3	4		×
1	2		×
552		0	1

