

A-5520BCS2

COMBILIGHT ON-OFF SWITCH SIGNAL CONTROLLED BICOLOR + BLINK. + BUZZER 24V 3P 12A



Code	009A-5520BCS2
EAN	8430892263672
Product description	Combilight bicolor switch disconnecter + flashing + buzzer by signal 24vdc, IP20 with 0-1 black front plate 48x48 for panel fixing, red-green LED. 3 poles 12A. Size D0. Ergonomic screwless quick-mount handle. Connection with cage terminals for 2.5-6 mm ² cable. Compatible with multiple accessories from the A5 series.

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	3
Operational rating (Ie)	12A
Thermal rating (Ith)	16 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm ²
Wire section flexible	2,5 - 6 mm ²
Tightening torque	1,6 Nm
Connection screws	M4

Terminal



Max. fuse protection (gG/aM)	25/25 A (415 V)
	25/25 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	400
Dummy AC-21A	3 kW (3x230 V)
	7,5 kW (3x415 V)
	11 kW (3x500 V)
Mixed load AC-22A	2,2 kW (3x230 V)
	5,5 kW (3x415 V)
	7,5 kW (3x500 V)
Motor load AC-23A	2,2 kW (3x230 V)
	4 kW (3x415 V)
	5,5 kW (3x500 V)
UL Electric characteristics	1 hp 1-phase (110-120 V)
	1,5 hp 1-phase (220-240 V)
	1 hp 3-phase (220-240 V)
	2 hp 3-phase (380-415 V)
	3 hp 3-phase (440-480 V)
	3 hp 3-phase (550-600 V)
Standard	IEC 60947-3
	UL 508

Connection

5	6		×
3	4		×
1	2		×
552		0	1

