

A-553912L

COMBILIGHT ON-OFF SWITCH RED/GREEN 230V 4P 125A



| | |
|----------------------------|---|
| Code | 009A-553912L |
| EAN | 8430892262484 |
| Product description | Combilight switch disconnecter by position 230vac, IP20 with 0-1 black front plate 64x64 for panel fixing, 0" red LED, "1" green LED. 4 poles 125A. Size D2. Ergonomic screwless quick-mount handle. Connection with cage terminals for 16-50 mm ² cable. Compatible with multiple accessories from the A5 series. " |


Logistic data

| | |
|---------------|----------|
| Customs code | 85365080 |
| ETIM code | EC000216 |
| Package units | 1 |

Technical data

| | |
|-------------------------|-------------------------|
| Operational rating (Ie) | 125 A |
| Thermal rating (Ith) | 125 A |
| Wire section (AWG) | 16 - 1 |
| Wire section flexible | 16 - 50 mm ² |
| Tightening torque | 3,5 Nm |
| Connection screws | M8 |

Terminal



| | |
|--|--------------------------|
| Max. fuse protection (gG/aM) | 125/100 A (415 V) |
| | 125/100 A (500 V) |
| Conditional shortcircuit current (Icc) | 8 kA (415 V) |
| | 8 kA (500 V) |
| Insulating voltage (V~) | 690 |
| Insulating voltage (V...) | 600 |
| Dummy AC-21A | 37 kW (3x230 V) |
| | 75 kW (3x415 V) |
| | 90 kW (3x500 V) |
| Mixed load AC-22A | 37 kW (3x230 V) |
| | 55 kW (3x415 V) |
| | 75 kW (3x500 V) |
| Motor load AC-23A | 18,5 kW (3x230 V) |
| | 37 kW (3x415 V) |
| | 45 kW (3x500 V) |
| UL Electric characteristics | 10 hp 1-fase (110-120 V) |
| | 15 hp 1-fase (220-240 V) |
| | 25 hp 3-fase (220-240 V) |
| | 30 hp 3-fase (380-415 V) |
| | 40 hp 3-fase (440-480 V) |
| | 50 hp 3-fase (550-600 V) |
| Standard | IEC 60947-3 |
| | UL 508 |

Connection

