AGB112211

TURN TO PUSH BICOLOR CHANGEOVER SWITCH 110VDC 1M 1S 25A. GREEN/RED



Code	009AGB112211
EAN	8430892279451
Product description	Discrepancy switch, bicolor type turn to push. Fixing 4 points 36x36 with central hole 40mm diammeter. Light frontal handle with leds green color in position 0-180º and red in position 90-270º, supply voltage 110vdc. 1 contact signal and 1 contact control rated 25A. Connection with cage terminals for 1,5-6mm² cable

Technical data

Operational rating (Ie)	25 A
Thermal rating (Ith)	25 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm2
Wire section flexible	2,5 - 6 mm2
Tightening torque	1,6 Nm
Connection screws	M4
Terminal	
Max. fuse protection (gG/aM)	25/25 A (415 V) 25/25 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V) 6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	400
Dummy AC-21A	7,5 kW (3x230 V) 15 kW (3x415 V) 18,5 kW (3x500 V)
Mixed load AC-22A	7,5 kW (3x230 V) 15 kW (3x415 V) 18,5 kW (3x500 V)
Motor load AC-23A	5,5 kW (3x230 V) 7,5 kW (3x415 V) 11 kW (3x500 V)
UL Electric characteristics	2 hp 1-fase (110-120 V) 3 hp 1-fase (220-240 V) 2 hp 3-fase (220-240 V) 3 hp 3-fase (380-415 V) 5 hp 3-fase (440-480 V) 7 hp 3-fase (550-600 V)
Standard	IEC 60947-3 UL 508