

AMB022201

BICOLOR CHANGEOVER SWITCH 2 SIGNAL 110VDC D0 25A GREEN/WHITE



| | |
|----------------------------|--|
| Code | 009AMB022201 |
| EAN | 8430892265553 |
| Product description | Discrepancy switch bicolor. Fixing 4 points 36x36 with central hole 40mm diameter. Light frontal handle with white leds color in position 0-180° and green in position 90-270°, supply voltage 110vdc. 2 contact signal rated 25A. Connection with cage terminals for 1,5-6mm ² cable |

Logistic data

Customs code 85365080

Technical data

| | |
|-------------------------|-------------------------|
| Operational rating (Ie) | 25 A |
| Thermal rating (Ith) | 25 A |
| Wire section (AWG) | 10 |
| Wire section rigid | 2,5 - 6 mm ² |
| Wire section flexible | 2,5 - 6 mm ² |
| Tightening torque | 1,6 Nm |
| Connection screws | M4 |

Terminal



| | |
|------------------------------|-----------------|
| Max. fuse protection (gG/aM) | 25/25 A (415 V) |
| | 25/25 A (500 V) |

| | |
|--|--------------|
| Conditional shortcircuit current (Icc) | 6 kA (415 V) |
| | 6 kA (500 V) |

| | |
|---------------------------|-----|
| Insulating voltage (V~) | 690 |
| Insulating voltage (V...) | 400 |

| | |
|--------------|-------------------|
| Dummy AC-21A | 7,5 kW (3x230 V) |
| | 15 kW (3x415 V) |
| | 18,5 kW (3x500 V) |

| | |
|-------------------|-------------------|
| Mixed load AC-22A | 7,5 kW (3x230 V) |
| | 15 kW (3x415 V) |
| | 18,5 kW (3x500 V) |

| | |
|-------------------|------------------|
| Motor load AC-23A | 5,5 kW (3x230 V) |
| | 7,5 kW (3x415 V) |
| | 11 kW (3x500 V) |

| | |
|-----------------------------|--------------------------|
| UL Electric characteristics | 2 hp 1-phase (110-120 V) |
| | 3 hp 1-phase (220-240 V) |
| | 2 hp 3-phase (220-240 V) |
| | 3 hp 3-phase (380-415 V) |
| | 5 hp 3-phase (440-480 V) |
| | 7 hp 3-phase (550-600 V) |

| | |
|----------|-------------|
| Standard | IEC 60947-3 |
| | UL 508 |
