

## AMB022201

BICOLOR CHANGEOVER SWITCH 2 SIGNAL 110VDC D0 25A GREEN/WHITE

<b>Code</b>	009AMB022201
<b>EAN</b>	8430892265553

---

**Product description**

Discrepancy switch bicolor. Fixing 4 points 36x36 with central hole 40mm diameter. Light frontal handle with white leds color in position 0-180° and green in position 90-270°, supply voltage 110vdc. 2 contact signal rated 25A. Connection with cage terminals for 1,5-6mm<sup>2</sup> cable

---

## Logistic data

---

Customs code 85365080

---

## Technical data

---

Operational rating (Ie)	25 A
Thermal rating (Ith)	25 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm <sup>2</sup>
Wire section flexible	2,5 - 6 mm <sup>2</sup>
Tightening torque	1,6 Nm
Connection screws	M4

---

Terminal



Max. fuse protection (gG/aM)	25/25 A (415 V)
	25/25 A (500 V)

---

Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)

---

Insulating voltage (V~)	690
-------------------------	-----

---

Insulating voltage (V...)	400
---------------------------	-----

---

Dummy AC-21A	7,5 kW (3x230 V)
	15 kW (3x415 V)
	18,5 kW (3x500 V)

---

Mixed load AC-22A	7,5 kW (3x230 V)
	15 kW (3x415 V)
	18,5 kW (3x500 V)

---

Motor load AC-23A	5,5 kW (3x230 V)
	7,5 kW (3x415 V)
	11 kW (3x500 V)

---

UL Electric characteristics	2 hp 1-phase (110-120 V)
	3 hp 1-phase (220-240 V)
	2 hp 3-phase (220-240 V)
	3 hp 3-phase (380-415 V)
	5 hp 3-phase (440-480 V)
	7 hp 3-phase (550-600 V)

---

Standard	IEC 60947-3
	UL 508

---