

AMS022000

SIGNAL DISCREPANCY SWITCH 25A 2S



| | |
|----------------------------|--|
| Code | 009AMS022000 |
| EAN | 8430892216364 |
| Product description | Discrepancy switch,. Fixing 4 points 36x36 with central hole 40mm diameter. Light frontal handle with white leds, supply multivoltage 24-240vac / 24-110vdc. 2 contact signal rated 25A. Connection with cage terminals for 1,5-6mm ² cable |

Logistic data

| | |
|---------------------|----------|
| Customs code | 85365080 |
| ETIM code | EC002611 |
| Package units | 1 |
| Package height (mm) | 95 |
| Package width (mm) | 68 |
| Package length (mm) | 68 |

Technical data

| | |
|-------------------------|-------------------------|
| Operational rating (Ie) | 25 A |
| Thermal rating (Ith) | 25 A |
| Wire section (AWG) | 10 |
| Wire section rigid | 2,5 - 6 mm ² |
| Wire section flexible | 2,5 - 6 mm ² |
| Tightening torque | 1,6 Nm |
| Connection screws | M4 |

Terminal



| | |
|--|-------------------------|
| Max. fuse protection (gG/aM) | 25/25 A (415 V) |
| | 25/25 A (500 V) |
| Conditional shortcircuit current (Icc) | 6 kA (415 V) |
| | 6 kA (500 V) |
| Insulating voltage (V~) | 690 |
| Insulating voltage (V...) | 400 |
| Dummy AC-21A | 7,5 kW (3x230 V) |
| | 15 kW (3x415 V) |
| | 18,5 kW (3x500 V) |
| Mixed load AC-22A | 7,5 kW (3x230 V) |
| | 15 kW (3x415 V) |
| | 18,5 kW (3x500 V) |
| Motor load AC-23A | 5,5 kW (3x230 V) |
| | 7,5 kW (3x415 V) |
| | 11 kW (3x500 V) |
| UL Electric characteristics | 2 hp 1-fase (110-120 V) |
| | 3 hp 1-fase (220-240 V) |
| | 2 hp 3-fase (220-240 V) |
| | 3 hp 3-fase (380-415 V) |
| | 5 hp 3-fase (440-480 V) |
| Standard | 7 hp 3-fase (550-600 V) |
| | IEC 60947-3 |
| | UL 508 |

Dimensions

