

AB5534107

ON-OFF SWITCH DISCONNECTOR 4P.40A. ENCLOSED IP65 PADLOCKABLE RED/YELLOW



Code	009AB5534107
EAN	8430892155830

Product description

4-pole 40A safety switch in IP65 enclosure. E0 polycarbonate enclosure suitable for indoor or outdoor use, RAL7035 grey cover and black base, dimensions 100x130x90. M20 easy-open knockouts, two on top, two on bottom and two at the base. 4 points surface fixing. Base mounted switch with extended shaft and interlock in closed position. Red / yellow padlockable handle (up to 4 padlocks of 8mm diameter). Earthing terminal. Connection with cage terminals for 6-16 mm² cable.

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1
Package height (mm)	130
Package width (mm)	135
Package length (mm)	100

Technical data

Poles	4
Operational rating (Ie)	40 A
Thermal rating (Ith)	40 A
Wire section (AWG)	6
Wire section rigid	6 - 25 mm ²
Wire section flexible	6 - 16 mm ²
Tightening torque	2 Nm
Connection screws	M5

Terminal



Max. fuse protection (gG/aM)	40/32 A (415 V)
	40/32 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	15 kW (3x230 V)
	22 kW (3x415 V)
	30 kW (3x500 V)
Mixed load AC-22A	11 kW (3x230 V)
	22 kW (3x415 V)
	22 kW (3x500 V)
Motor load AC-23A	11 kW (3x230 V)
	18,5 kW (3x415 V)
	22 kW (3x500 V)
UL Electric characteristics	2 hp 1-fase (110-120 V)
	5 hp 1-fase (220-240 V)
	7,5 hp 3-fase (220-240 V)
	10 hp 3-fase (380-415 V)
	15 hp 3-fase (440-480 V)
	20 hp 3-fase (550-600 V)
Standard	IEC 60947-3
	UL 508
Enclosure type	PLASTIC

Connection



Dimensions

