

AC553910C

ON-OFF SWITCH DISCONNECTOR 4P.125A. PC ENCLOSED IP65 PADLOCKABLE GREY/BLACK + EMC



Code	009AC553910C
EAN	8430892351089
Product description	4-pole 125A safety switch in IP65 enclosure. E3 sheet steel enclosure suitable for indoor or outdoor use in RAL7035 grey color, dimensions 300x400x200. High impact resistance IK10. Base mounted switch with extended shaft and interlock in closed position. Metal shielding plate for EMC electromagnetic compatibility. Grey / Black padlockable handle (up to 4 padlocks of 8mm diameter). Earthing terminal. Connection with cage terminals for 16-50 mm ² cable.

Dimensions

Product height	300
Product width	400
Product length	200



Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	4
Operational rating (Ie)	125
Thermal rating (Ith)	125 A
Wire section (AWG)	16 - 1
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8
Terminal	
Max. fuse protection (gG/aM)	125/100 A (415 V) 125/100 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V) 8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	37 kW (3x230 V) 75 kW (3x415 V) 90 kW (3x500 V)
Mixed load AC-22A	37 kW (3x230 V) 75 kW (3x415 V) 90 kW (3x500 V)
Motor load AC-23A	30 kW (3x230 V) 55 kW (3x415 V) 55 kW (3x500 V)
UL Electric characteristics	10 hp 1-fase (110-120 V) 15 hp 1-fase (220-240 V) 25 hp 3-fase (220-240 V) 30 hp 3-fase (380-415 V) 40 hp 3-fase (440-480 V) 50 hp 3-fase (550-600 V)
Standard	IEC 60947-3 UL 508
Enclosure type	METAL

Connection



Dimensions

