

## AB55261F4

ON-OFF SWITCH DISCONNECTOR 3P 63A D2 F400 PROTEC



<b>Code</b>	009AB55261F4
<b>EAN</b>	8430892223201

---

**Product description**

3 pole 63A switch disconnecter fire rated class F400 according to EN 12101-3. Enclosure 4AL in aluminium painted in grey color RAL7040 with surface coating to protect against corrosion, dimensions 250x250x111. Protection degree IP65. Threaded M40 holes, one on top and one on bottom. Fixing to the surface by 4 points. Red / Yellow padlockable handle (up to 4 padlocks of 8mm diameter). Connection with cage terminals for 16-35mm<sup>2</sup> cable.

---

## Dimensions

Product height	250
Product width	250
Product length	111

## Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1
Product gross weight (kg)	1.72
Package height (mm)	150
Package width (mm)	170
Package length (mm)	205

## Technical data

Poles	3
Operational rating (Ie)	63 A
Thermal rating (Ith)	70 A
Wire section flexible	16 - 50 mm <sup>2</sup>
Tightening torque	3,5 Nm
Connection screws	M8

### Terminal



Max. fuse protection (gG/aM)	63/63 A (415 V)
	63/63 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V~)	690
	600
	22 kW (3x230 V)
Dummy AC-21A	45 kW (3x415 V)
	45 kW (3x500 V)
	18,5 kW (3x230 V)
Mixed load AC-22A	37 kW (3x415 V)
	45 kW (3x500 V)
	18,5 kW (3x230 V)
Motor load AC-23A	30 kW (3x415 V)
	37 kW (3x500 V)
	18,5 kW (3x230 V)
Standard	IEC 60947-3
	EN 12101-3
Fire Rating	F400

## Connection

5	6		×
3	4		×
1	2		×
552		0	1



## Dimensions

