

AB55641F4

FIRE-RATED SWITCH F400 6P 40A



Code	009AB55641F4
EAN	8430892237901

Product description

6 pole 40A switch disconnecter fire rated class F400 according to EN 12101-3. Enclosure 3AL in aluminium painted in grey color RAL7040 with surface coating to protect against corrosion, dimensions 160x160x90. Protection degree IP65. Threaded M32 holes, two on top and two on bottom. Fixing to the surface by 4 points. Red / Yellow padlockable handle (up to 4 padlocks of 8mm diameter). Connection with cage terminals for 6-16mm² cable.

Dimensions

Product height	160
Product width	160
Product length	90

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1
Product gross weight (kg)	1.45
Package height (mm)	150
Package width (mm)	170
Package length (mm)	205

Technical data


Poles	6
Operational rating (Ie)	40 A
Thermal rating (Ith)	40 A
Wire section rigid	6 - 25 mm ²
Wire section flexible	6 - 16 mm ²
Tightening torque	2 Nm
Connection screws	M5

Terminal



Max. fuse protection (gG/aM)	40/32 A (415 V)
	40/32 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	15 kW (3x230 V)
	22 kW (3x415 V)
	30 kW (3x500 V)
Mixed load AC-22A	11 kW (3x230 V)
	22 kW (3x415 V)
	22 kW (3x500 V)
Motor load AC-23A	11 kW (3x230 V)
	18,5 kW (3x415 V)
	22 kW (3x500 V)
Standard	30 kW (3x690 V)
	IEC 60947-3
	EN 12101-3
Fire Rating	F400

Connection



Dimensions

