

L475J9100

BYPASS LD CHANGEOVER SWITCH 3P+6P 125A +AC WITH OVERLAPPING

Code

009L475J9100


Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	3
Auxiliary	1NO
Operational rating (Ie)	125 A
Thermal rating (Ith)	125 A
Wire section (AWG)	16 - 1
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	125/100 A (415 V) 125/100 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V) 8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	37 kW (3x230 V) 75 kW (3x415 V) 90 kW (3x500 V)
Mixed load AC-22A	37 kW (3x230 V) 55 kW (3x415 V) 75 kW (3x500 V)
Motor load AC-23A	30 kW (3x230 V) 55 kW (3x415 V) 55 kW (3x500 V)
Standard	IEC 60947-3

Connection

n.º de ref. 475J Coaxial	L1 1 3 		F 5 7 		E 9 11 		L2 13 15 		L3 17 19 		G 21 23 		25 27 		29 31 		33 35 		37 39 		41 43 		45 47 				
	A 2 4 		S1 6 8 		S2 10 12 		B 14 16 		C 18 20 		S3 22 24 		26 28 		30 32 		34 36 		38 40 		42 44 		46 48 				
	O		O		O		O		O		O		O		O		O		O		O		O				
1- I	X		X	X			X	X			X																
2- I + AUX	X		X	X			X	X			X	X															
3- I+II+AUX	X	X	X	X			X	X			X	X															
4- II+AUX		X					X				X			X													
5-																											
6-																											
7-																											
8-																											
9-																											
10-																											
11-																											
12-																											
X contacto cerrado		X contacto cerrado en varias posiciones sin interrupción		↪ retorno de la última posición a la anterior																							



Dimensions

