

L479J6100

LD BYPASS CHANGEOVER SWITCH 4P+8P 63A +AC WITH OVERLAPPING

Code

009L479J6100

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1
Package height (mm)	150
Package width (mm)	195
Package length (mm)	280

Technical data

Poles	4
Auxiliary	1NO
Operational rating (Ie)	63 A
Thermal rating (Ith)	70 A
Wire section (AWG)	16 - 1
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	63/63 A (415 V) 63/63 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V) 8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	22 kW (3x230 V) 45 kW (3x415 V) 45 kW (3x500 V)
Mixed load AC-22A	18,5 kW (3x230 V) 37 kW (3x415 V) 45 kW (3x500 V)
Motor load AC-23A	18,5 kW (3x230 V) 30 kW (3x415 V) 37 kW (3x500 V)
Standard	IEC 60947-3

Connection

n.º de ref.
479J
Coaxial

L1	1	3	F	5	7	E	9	11	L2	13	15	H	17	19	G	21	23	N	25	27	29	31	33	35	37	39	41	43	45	47	
	2	4	S2	6	8	S2	10	12	B	14	16	C	18	20	S3	22	24	Sn	D	26	28	30	32	34	36	38	40	42	44	46	48

1- I	X		X	X	X		X	X	X	X	X	X	X	X	X	X	X														
2- I+AUX	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X												
3- I+II+AUX	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X											
4- II+AUX		X					X				X				X		X		X												
5-																															
6-																															
7-																															
8-																															
9-																															
10-																															
11-																															
12-																															

X contacto cerrado

X contacto cerrado en varias posiciones sin interrupción

↶ retorno de la última posición a la anterior



Dimensions

