

AK1504006

ALUMINIUM ENCLOSURE D2 UP TO 4 CELLS



Code	009AK1504006
EAN	8430892257855
Product description	Aluminum enclosure with IP65 protection and high impact resistance IK09. RAL7040 grey color. Stainless steel screws. Dimensions 250x250x111 for D2 size switches up to 4 cells. Two M40 holes, one on top and one bottom. Earthing terminal on the base and on the cover.

Logistic data

Customs code	85371099
ETIM code	EC002600
Package units	1

Technical data

Operational rating (Ie)	125 A
Thermal rating (Ith)	125 A
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	125/100 A (415 V)
	125/100 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V...)	600
Dummy AC-21A	37 kW (3x230 V)
	75 kW (3x415 V)
	90 kW (3x500 V)
Mixed load AC-22A	37 kW (3x230 V)
	55 kW (3x415 V)
	75 kW (3x500 V)
Motor load AC-23A	30 kW (3x230 V)
	55 kW (3x415 V)
	55 kW (3x500 V)
UL Electric characteristics	10 hp 1-fase (110-120 V)
	15 hp 1-fase (220-240 V)
	25 hp 3-fase (220-240 V)
	30 hp 3-fase (380-415 V)
	40 hp 3-fase (440-480 V)
	50 hp 3-fase (550-600 V)

Dimensions

